RECEIVED CENTRAL FAX CENTER

NUV 1 5 2006

Serial No: 10/647,313 Art Unit: 1616 Response to Office Action mailed 07/19/2006

IN THE CLAIMS

- (currently amended) A sheeted self-tanning composition application dispensing set comprising of a plurality of sheeted-like substrates and a dispensing enclosure; wherein each of said sheeted-like substrates is infused with an aqueous self-tanning composition; and
 - wherein said plurality of sheeted-like substrates is arranged in said dispensing enclosure for dispensing therefrom one sheet at a time;
 - wherein each said sheeted-like substrate is such that said aqueous self-tanning composition adheres thereto when said sheeted-like substrate is within said dispensing enclosure, and is such that said aqueous self-tanning composition will transfer therefrom when said sheeted-like substrate is applied to the skin of a user;
 - and wherein said aqueous self-tanning composition comprises from 45% to 65% by weight of aqueous extract of Japanese green tea, from 5% to 15% by weight of dihydroxyacetone, from 5% to 25% by weight of ethoxydiglycol, from 3% to 10% by weight of PPG-12-Buteth-16 as an emollient, from 1% to 13% by weight of a humectant, and from 0.05% to 0.5%, by weight of cosmetically acceptable and compatible minerals.
- 2. (original) The sheeted self-tanning composition application dispensing set of claim 1, wherein said self-tanning composition further comprises further cosmetically acceptable and compatible additives chosen from the group consisting of from 0.5% to 5% by weight of bacillus ferment as an enzyme exfoliator, from 0.5% to 5% by weight of frankincense extract as a moisturizer, from 0.1% to 7.5% by weight of a skin protectant, from 0.1% to 6% by weight of a cosmetically acceptable and compatible colorant, from 0.5% to 1.5% by weight of tocopherol as an anti-oxidant, from 0.1% to 1% by weight of disodium ethylenediamine tetraacidic acid (EDTA), from 1% to 5% by weight of a tanning accelerator, from 0.5% to 1% by weight of a cosmetically acceptable and compatible preservative, from 0.5% to 1% by weight of PPG-40-castor oil as a stabilizer, from 0.1% to 0.5% by weight of natural essential oils, and mixtures thereof.
 - 3. (original) The sheeted self-tanning composition application dispensing set of claim

Scrial No: 10/647.313

Art Unit: 1616

- 2, wherein said humectant is chosen from the group consisting of 1% to 5% by weight of butylene glycol, from 1% to 8% by weight of glycerine, and mixtures thereof;
 - wherein said skin protectant is chosen from the group consisting of 0.5% 5 to 2.5% by weight of aloe vera gel, from 0.5% to 4% by weight of hydrocotyl extract, from 0.1% to 1% by weight of myrrh extract, and mixtures thereof;
 - wherein said cosmetically acceptable and compatible colorant is chosen from the group consisting of 1% to 5% by weight of walnut extract, 0.1% to 1% by weight of caramel, and mixtures thereof, together with said minerals;
 - wherein said minerals are chosen from the group consisting of C.I. #15985, #77492, #77491, #77499, #77718, #42090, #16035, and mixtures thereof;
 - wherein said tanning accelerator is chosen from the group consisting of acetyl-Ltyrosine, hydrolyzed vegetable protein, adenosine triphosphate, riboflavin, and mixtures thereof;
 - and wherein said cosmetically acceptable and compatible preservative is chosen from the group consisting of methyl paraben, dimethylol dimethyl hydantoin, and iodopropynyl butylcarbamate, and mixtures thereof.
- 4. (original) The sheeted self-tanning composition application dispensing set of claim 1, wherein said self-tanning composition further comprises from 0.5% to 20% by weight of sunscreen chosen from the group consisting of from 1% to 20% by weight of octyl methoxycinnamate, from 1% to 20% by weight of octyl salicylate, from 1% to 10% by weight of benzophenone-3, from 0.5% to 10% by weight of benzophenone-4, and mixtures thereof.
- 5. (currently amended) The sheeted self-tanning composition application dispensing set of claim 1, wherein the material of said plurality of sheeted-like substrates is chosen from the group consisting of woven fabrics, non-woven fabrics, paper, cellulose, and mixtures thereof.
- 6. (original) The sheeted self-tanning composition application dispensing set of claim 5, wherein said fabrics have a composition which comprises from 20% to 80% by weight of polypropylene, and from 20% to 80% by weight of viscose rayon.

Art Unit: 1616

- 7. (currently amended) The sheeted self-tanning composition application dispensing set of claim 1, wherein said plurality of sheet<u>ed-like</u> substrates is arranged in a manner chosen from the group consisting of a plurality of sheet<u>ed-like</u> substrates rolled in sheets which are separable at perforations therebetween, interleaved sheets, stacked sheets, and stacked folded sheets.
- 8. (original) The sheeted self-tanning composition application dispensing set of claim 7, wherein said dispensing enclosure is chosen from the group consisting of sealable canisters having a cruciform dispensing opening formed at one end thereof, sealable boxes having a reclosable lid at the top thereof, resealable pouches having a dispensing slit on one side surface thereof, and resealable pouches having a resealable opening at one end thereof.
- 9. (currently amended) The sheeted self-tanning composition application dispensing set of claim 1, wherein each one of said plurality of sheeted-like substrates is rectangular, and has a size in the range of 7.5 cm by 7.5 cm up to 25 cm by 25 cm.
- 10. (currently amended) The sheeted self-tanning composition application dispensing set of claim 9, wherein each one of said plurality of sheeted-like substrates is infused with an amount of said aqueous self-tanning composition in the range of 0.015 g/cm² to 0.022 g/cm².
- 11. (currently amended) A method of infusing a plurality of sheeted-like substrates with an aqueous self-tanning composition;
 - wherein each of said plurality of sheeted like substrates has a surface area in the range of from 55 cm² to 625 cm²;
 - wherein the material of said plurality of sheeted like substrates is chosen from the group consisting of woven fabrics, non-woven fabrics, paper, cellulose, and mixtures thereof;

Art Unit: 1616

Response to Office Action mailed 07/19/2006

wherein each one of said plurality of sheet<u>ed-like</u> substrates is infused with an amount of said aqueous self-tanning composition in the range of 0.015 g/cm² to 0.022 g/cm²;

and wherein said aqueous self-tanning composition comprises from 45% to 65% by weight of aqueous extract of Japanese green tea, from 5% to 15% by weight of dihydroxyacetone, from 5% to 25% by weight of ethoxydiglycol, from 3% to 10% by weight of PPG-12-Buteth-16 as an emollient, from 1% to 13% by weight of a humectant, and from 0.05% to 0.5% by weight of cosmetically acceptable and compatible minerals;

wherein said method comprises the steps of:

- (a) placing a plurality of sheeted-like substrates in a sealable vacuum chamber, wherein said sealable vacuum chamber has agitation means in the interior thereof to cause agitated movement of said plurality of sheeted-like substrates when placed therein, wherein said sealable vacuum chamber is capable of being rotated about an axis so as to cause a tumbling movement of said plurality of sheeted-like substrates when placed therein, and wherein said sealable vacuum chamber has an injection port;
- (b) sealing said vacuum chamber;
- (c) heating the interior of said vacuum chamber to a temperature of 105° C. to 115° C., and maintaining that temperature for a period of from 30 to 35 minutes, while tumbling and agitating said plurality of sheeted like substrates;
- (d) cooling said interior of said vacuum chamber to a temperature of 70° C. to 75° C., at a rate of 5° C. per 15 minutes;
- (e) drawing a vacuum in the interior of said vacuum chamber to a gauge vacuum in the range of 27 cm Hg to 42 cm Hg;
- (f) introducing said aqueous extract of Japanese green tea into said vacuum chamber while maintaining said temperature of step (d), and tumbling and agitating said plurality of sheeted-like substrates for a period of 20 to 25 minutes;
- (g) cooling said interior of said vacuum chamber to a temperature in the range of 62° C. to 67° C., at a rate of 5° C. per 15 minutes;

Art Unit: 1616

- (h) introducing said humectant into said vacuum chamber while maintaining said temperature of step (g), and tumbling and agitating said plurality of sheeted-like substrates for a period of 12 to 18 minutes;
- (i) cooling said interior of said vacuum chamber to a temperature of 48° C. to 52° C., at a rate of 5° C. per 15 minutes;
- (j) introducing said minerals into said vacuum chamber while maintaining said temperature of step (i), and tumbling and agitating said plurality of sheeted-like substrates for a period of 28 to 38 minutes;
- (k) cooling said interior of said vacuum chamber to a temperature of 43° C. to 47° C., at a rate of 5° C. per 15 minutes;
- premixing said ethoxydiglycol and said PPG-12-Buteth-16, and adding said dihydroxyacetone thereto, to form a homogenous mixture;
- (m) introducing said homogenous mixture into said vacuum chamber while maintaining said temperature of step (k), and tumbling and agitating said plurality of sheeted-like substrates for a period of 38 to 48 minutes;
- (n) cooling said interior of said vacuum chamber to a temperature of 28° C. to 32° C., at a rate of 5° C. per 15 minutes;
- (o) relieving said vacuum, opening said vacuum chamber, and removing said plurality of infused sheet<u>ed-like</u> substrates therefrom for packaging in groups of pluralities thereof into dispensing enclosures therefor.
- 12. (original) The method of claim 11, wherein said sealable vacuum chamber has a double-walled structure, and step (c) is carried out by injecting steam into the chamber formed by and between the two walls of said double-walled structure.
- 13. (original) The method of claim 11, wherein said self-tanning composition further comprises further cosmetically acceptable and compatible additives chosen from the group consisting of from 0.5% to 5% by weight of bacillus ferment as an enzyme exfoliator, from 0.5% to 5% by weight of frankincense extract as a moisturizer, from 0.1% to 7.5% by weight of a skin protectant, from 0.1% to 6% by weight of a cosmetically acceptable and compatible colorant, from 0.5% to 1.5% by weight of tocopherol as an anti-oxidant, from 0.1% to 1% by weight of disodium ethylenediamine

Scrint No: 10/647,313

Art Unit: 1616

Response to Office Action mailed 07/19/2006

tetraacidic acid (EDTA), from 1% to 5% by weight of a tanning accelerator, from 0.5% to 1% by weight of a cosmetically acceptable and compatible preservative, from 0.5% to 1% by weight of PPG-40-castor oil as a stabilizer, from 0.1% to 0.5% by weight of natural essential oils, and mixtures thereof.

- 14. (original) The method of claim 12, wherein said humectant is chosen from the group consisting of 1% to 5% by weight of butylene glycol, from 1% to 8% by weight of glycerine, and mixtures thereof;
 - wherein said skin protectant is chosen from the group consisting of 0.5% to 2.5% by weight of aloe vera gel, from 0.5% to 4% by weight of hydrocotyl extract, from 0.1% to 1% by weight of myrrh extract, and mixtures thereof;
 - wherein said cosmetically acceptable and compatible colorant is chosen from the group consisting of 1% to 5% by weight of walnut extract, 0.1% to 1% by weight of caramel, and mixtures thereof, together with said minerals;
 - wherein said minerals are chosen from the group consisting of C.I. #15985, #77492, #77491, #77499, #77718, #42090, #16035, and mixtures thereof;
 - wherein said tanning accelerator is chosen from the group consisting of acetyl-L-tyrosine, hydrolyzed vegetable protein, adenosine tripbosphate, riboflavin, and mixtures thereof;
 - and wherein said cosmetically acceptable and compatible preservative is chosen from the group consisting of methyl paraben, dimethylol dimethyl hydantoin, and iodopropynyl butylcarbamate, and mixtures thereof.
 - 15. (currently amended) The method of claim 13, further comprising the step of:
 - (p) after step (m), cooling said interior of said vacuum chamber to a temperature of 35° C. to 39° C. at a rate of 5° C. per 15 minutes;
 - and wherein said method further comprises further steps carried out after step (p) and before step (n);
 - wherein said further steps are chosen from the group consisting of the following steps, and mixtures thereof:

Art Unit: 1616

- (q) introducing said bacillus ferment into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheetedlike substrates for a period of 12 to 18 minutes;
- (r) introducing said frankincense extract into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheeted-like substrates for a period of 12 to 18 minutes;
- (s) introducing said skin protectant into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheeted like substrates for a period of 12 to 18 minutes;
- (t) introducing said cosmetically acceptable and compatible colorant into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheeted-like substrates for a period of 12 to 18 minutes;
- (u) introducing said anti-oxidant into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheeted-like substrates for a period of 12 to 18 minutes;
- (v) introducing said EDTA into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheeted-like substrates for a period of 12 to 18 minutes;
- (w) introducing said tanning accelerator into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheetedlike substrates for a period of 12 to 18 minutes;
- (x) introducing said cosmetically acceptable and compatible preservative into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheeted-like substrates for a period of 12 to 18 minutes;
- (y) introducing said stabilizer into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheeted-like substrates for a period of 12 to 18 minutes; and
- (z) introducing said natural essential oils into said vacuum chamber while maintaining said temperature of step (p), and tumbling and agitating said plurality of sheeted-like substrates for a period of 12 to 18 minutes.

Art Unit: 1616

Response to Office Action mailed 07/19/2006

16. (original) The method of claim 15, wherein said self-tanning composition further comprises from 0.5% to 20% by weight of sunscreen chosen from the group consisting of from 1% to 20% by weight of octyl methoxycinnamate, from 1% to 20% by weight of octyl salicylate, from 1% to 10% by weight of benzophenone-3, from 0.5% to 10% by weight of benzophenone-4, and mixtures thereof;

wherein said sunscreen is introduced into said vacuum chamber following step (q); and wherein said plurality of sheeted like substrates are tumbled and agitated for a period of from 28 to 38 minutes.

17. (new) A sheeted substrate infused with an aqueous self-tanning composition such that said aqueous self-tanning composition adheres thereto will transfer therefrom when said sheeted substrate is applied to the skin of a user, wherein:

said aqueous self-tanning composition comprises from 45% to 65% by weight of aqueous extract of Japanese green tea, from 5% to 15% by weight of dihydroxyacetone, from 5% to 25% by weight of ethoxydiglycol, from 3% to 10% by weight of PPG-12-Buteth-16 as an emollient, from 1% to 13% by weight of a humectant, and from 0.05% to 0.5%, by weight of cosmetically acceptable and compatible minerals.

the material of said sheeted substrates is chosen from the group consisting of woven fabrics, non-woven fabrics, paper, cellulose, and mixtures thereof; and each one of said plurality of sheeted substrates is infused with an amount of said aqueous self-tanning composition in the range of 0.015 g/cm² to 0.022 g/cm².